

屋内照明器具特性	
品番 (品名)	NNN62500
光源	LDA5L-G-E17/D/S/K4 ×1 440.0 l m
管理番号	K0184897 (1) DB 1
BZ分類	BZ2/2.3/BZ3

器具効率		5 4 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数		照明率 (X 0 . 0 1) Z C M															
保守率		良 中 否	0 . 6 7	0 . 6	3 6	3 1	2 7	2 5	3 5	3 0	2 7	2 5	3 4	3 0	2 7	2 5	3 3	2 9	2 7	2 5	2 4
			0 . 6 3	0 . 8	4 1	3 6	3 3	3 0	4 0	3 6	3 3	3 0	3 9	3 5	3 2	3 0	3 8	3 5	3 2	3 0	2 9
			0 . 5 6	1 . 0	4 4	4 0	3 7	3 4	4 3	3 9	3 6	3 4	4 2	3 9	3 6	3 4	4 1	3 8	3 6	3 4	3 3
				1 . 2 5	4 7	4 3	4 0	3 8	4 6	4 2	4 0	3 8	4 5	4 2	3 9	3 7	4 4	4 1	3 9	3 7	3 6
下方投影面積		c m ²	1 . 5	4 9	4 5	4 2	4 0	4 8	4 5	4 2	4 0	4 7	4 4	4 2	4 0	4 5	4 3	4 1	3 9	3 8	
			2 . 0	5 1	4 8	4 6	4 4	5 0	4 8	4 5	4 4	4 9	4 7	4 5	4 3	4 8	4 6	4 4	4 3	4 2	
取付 高さ	器具間隔最大限		2 . 5	5 2	5 0	4 8	4 6	5 2	4 9	4 7	4 6	5 0	4 8	4 7	4 5	4 9	4 7	4 6	4 5	4 4	
	横方向 (A) 縦方向 (B)		3 . 0	5 3	5 1	4 9	4 8	5 3	5 1	4 9	4 8	5 1	5 0	4 8	4 7	5 0	4 9	4 7	4 6	4 5	
H m	1 . 1 4 H m	1 . 1 4 H m	4 . 0	5 5	5 3	5 1	5 0	5 4	5 2	5 1	5 0	5 2	5 1	5 0	4 9	5 1	5 0	4 9	4 8	4 7	
			5 . 0	5 5	5 4	5 3	5 2	5 5	5 3	5 2	5 1	5 3	5 2	5 1	5 0	5 2	5 1	5 0	5 0	4 8	
			7 . 0	5 6	5 5	5 4	5 3	5 5	5 4	5 4	5 3	5 4	5 3	5 3	5 2	5 3	5 2	5 2	5 1	5 0	
			1 0 . 0	5 7	5 6	5 5	5 5	5 6	5 5	5 5	5 4	5 5	5 4	5 4	5 3	5 4	5 3	5 3	5 2	5 1	

