

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 0
光源	NNU141105LE9 ×1 1110.0 lm
管理番号	K0132244 (2) DR 1
B Z 分類	BZ1 / 1.4 / BZ2 / 8.5 / BZ1

器具効率		93 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) Z CM																				
保守率		良 中 否	0.81	0.6	67	59	53	50	66	58	53	50	64	57	53	50	63	57	53	49	48				
			0.77	0.8	75	67	62	59	74	67	62	59	72	66	62	58	70	65	61	58	57				
			0.68	1.0	80	73	68	65	79	73	68	65	77	71	67	64	75	70	67	64	62				
				1.25	84	78	74	70	83	78	73	70	81	76	73	70	79	75	72	69	68				
下方投影面積		cm ²		1.5	87	82	77	74	86	81	77	74	84	79	76	73	82	78	75	73	71				
				2.0	90	86	83	80	89	85	82	79	87	84	81	79	85	82	80	78	76				
等価発光面積		cm ²		2.5	93	89	86	83	91	88	85	83	89	86	84	82	87	85	83	81	79				
				3.0	94	91	88	86	93	90	87	85	91	88	86	84	89	87	85	83	81				
H m	0.76 H m		0.76 H m	4.0	96	93	91	89	95	92	90	89	92	91	89	87	90	89	87	86	84				
				5.0	97	95	93	91	96	94	92	91	94	92	91	89	92	90	89	88	86				
				7.0	98	97	95	94	97	96	94	93	95	94	93	92	93	92	91	90	88				
				10.0	99	98	97	96	98	97	96	95	96	95	94	93	94	93	92	92	89				

