

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 0
光源	NNU241105LE9 ×1 2010.0 lm
管理番号	K0133643 (3) DR 1
B Z 分類	BZ1 / 1.4 / BZ2 / 8.5 / BZ1

器具効率		93 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束 下方光束		93 %	室指数	照明率 (X0.01) Z CM																	
保守率		良 中 否	0.6	67	59	53	50	66	58	53	50	64	57	53	50	63	57	53	49	48	
			0.8	75	67	62	59	74	67	62	59	72	66	62	58	70	65	61	58	57	
			1.0	80	73	68	65	79	73	68	65	77	71	67	64	75	70	67	64	62	
			1.25	84	78	74	70	83	78	73	70	81	76	73	70	79	75	72	69	68	
下方投影面積 等価発光面積		cm ² cm ²	1.5	87	82	77	74	86	81	77	74	84	79	76	73	82	78	75	73	71	
			2.0	90	86	83	80	89	85	82	79	87	84	81	79	85	82	80	78	76	
取付 高さ	器具間隔最大限		2.5	93	89	86	83	91	88	85	83	89	86	84	82	87	85	83	81	79	
	横方向 (A) 縦方向 (B)		3.0	94	91	88	86	93	90	87	85	91	88	86	84	89	87	85	83	81	
H m	0.76 H m	0.76 H m	4.0	96	93	91	89	95	92	90	89	92	91	89	87	90	89	87	86	84	
			5.0	97	95	93	91	96	94	92	91	94	92	91	89	92	90	89	88	86	
			7.0	98	97	95	94	97	96	94	93	95	94	93	92	93	92	91	90	88	
			10.0	99	98	97	96	98	97	96	95	96	95	94	93	94	93	92	92	89	

