

屋内照明器具特性	
品番 (品名)	NNN71500
光源	NNU241115KLE9 x1 1840.0 l m
管理番号	K0190786 (0) DB 1
B Z 分類	BZ2 / 4.5 / BZ3 / 6.0 / BZ2

器具効率		89 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束		0 %		床	10 %				10 %				10 %				10 %				0 %
下方光束		89 %	室指数	照明率 (X0.01)																Z C M	
保守率		良 中 否	0.6	60	52	46	42	59	51	46	42	58	50	45	42	56	50	45	42	40	
			0.8	69	61	55	51	67	60	55	51	65	59	54	51	64	58	54	51	49	
			1.0	74	67	61	58	73	66	61	57	71	65	60	57	69	64	60	57	55	
			1.25	78	72	67	63	77	71	67	63	75	70	66	63	73	69	65	62	61	
下方投影面積		cm ²	1.5	81	76	71	68	80	75	71	67	78	73	70	67	76	72	69	66	65	
等価発光面積		cm ²	2.0	85	80	77	74	84	80	76	73	82	78	75	72	80	77	74	72	70	
取付 高さ	器具間隔最大限		2.5	87	83	80	77	86	83	80	77	84	81	78	76	82	79	77	75	73	
	横方向 (A) 縦方向 (B)		3.0	89	86	83	80	88	85	82	80	86	83	81	79	83	81	79	78	76	
H m	0.72 H m	0.72 H m	4.0	91	88	86	84	90	87	85	83	88	86	84	82	85	84	82	81	79	
			5.0	92	90	88	86	91	89	87	85	89	87	86	84	87	85	84	83	81	
			7.0	93	92	90	89	92	91	89	88	90	89	88	87	88	87	86	85	83	
			10.0	94	93	92	91	93	92	91	90	91	90	89	89	89	88	88	87	85	

