

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 0
光源	NNU141155KLE9 x1 1610.0 l m
管理番号	K0190789 (0) DB 1
B Z 分類	BZ2 / 4.5 / BZ3 / 6.0 / BZ2

器具効率		89 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01)																				Z C M
保守率		良 中 否	0.81	0.6	60	52	46	42	59	51	46	42	58	50	45	42	56	50	45	42	40				
			0.77	0.8	69	61	55	51	68	60	55	51	66	59	54	51	64	58	54	51	49				
			0.68	1.0	74	67	61	58	73	66	61	57	71	65	60	57	69	64	60	57	55				
				1.25	78	72	67	63	77	71	67	63	75	70	66	63	73	69	65	62	61				
下方投影面積		cm ²		1.5	81	76	71	68	80	75	71	67	78	73	70	67	76	72	69	66	65				
			等価発光面積	cm ²	2.0	85	81	77	74	84	80	76	73	82	78	75	72	80	77	74	72	70			
取付 高さ	器具間隔最大限			2.5	87	84	80	77	86	83	80	77	84	81	78	76	82	79	77	75	73				
	横方向 (A) 縦方向 (B)			3.0	89	86	83	80	88	85	82	80	86	83	81	79	84	81	79	78	76				
H m	0.73 H m 0.73 H m			4.0	91	88	86	84	90	87	85	83	88	86	84	82	86	84	82	81	79				
				5.0	92	90	88	86	91	89	87	86	89	87	86	84	87	85	84	83	81				
				7.0	93	92	90	89	92	91	90	88	90	89	88	87	88	87	86	85	83				
				10.0	94	93	92	91	93	92	91	90	91	90	90	89	89	89	88	87	85				

