

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 0
光源	NNU140105KLE9 x1 1130.0 l m
管理番号	K0190791 (0) DB 1
B Z 分類	BZ2

器具効率		91 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.81	0.6	61	52	47	43	60	52	47	43	59	51	46	43	57	50	46	42	41
			0.77	0.8	70	62	57	53	69	62	57	53	67	61	56	53	66	60	56	53	51
			0.68	1.0	76	69	64	60	75	68	63	60	73	67	63	59	71	66	62	59	58
				1.25	81	74	70	66	79	74	69	66	77	72	68	65	75	71	68	65	63
下方投影面積		c m ²		1.5	83	78	74	70	82	77	73	70	80	76	72	69	78	74	71	69	67
				2.0	87	83	79	76	86	82	78	76	84	80	77	75	82	79	76	74	72
取付高さ	器具間隔最大限			2.5	90	86	83	80	88	85	82	79	86	83	81	78	84	82	79	78	76
	横方向 (A)	縦方向 (B)		3.0	91	88	85	82	90	87	84	82	88	85	83	81	86	84	82	80	78
H m	1.20 H m	1.20 H m		4.0	93	90	88	86	92	89	87	85	90	88	86	84	88	86	84	83	81
				5.0	94	92	90	88	93	91	89	88	91	89	88	86	89	87	86	85	83
				7.0	95	94	92	91	94	93	92	90	92	91	90	89	90	89	88	87	85
				10.0	96	95	94	93	95	94	93	92	93	92	92	91	91	90	90	89	87

