

屋内照明器具特性	
品番 (品名)	NNN71500
光源	NNU140115KLE9 x1 1020.0 lm
管理番号	K0190792 (0) DB 1
BZ分類	BZ2

器具効率		91 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.81	0.6	61	52	47	43	60	52	46	43	59	51	46	43	57	50	46	42	41
			0.77	0.8	70	62	57	53	69	62	57	53	67	61	56	53	65	60	56	52	51
			0.68	1.0	76	69	64	60	75	68	63	60	73	67	63	59	71	66	62	59	57
				1.25	80	74	69	66	79	73	69	66	77	72	68	65	75	71	67	65	63
下方投影面積		cm ²		1.5	83	78	73	70	82	77	73	70	80	76	72	69	78	74	71	69	67
				2.0	87	83	79	76	86	82	78	75	84	80	77	75	82	79	76	74	72
等価発光面積		cm ²		2.5	89	86	82	80	88	85	82	79	86	83	80	78	84	81	79	77	75
				3.0	91	88	85	82	90	87	84	82	87	85	83	81	85	83	81	80	78
H m	1.19 H m	1.19 H m		4.0	93	90	88	86	92	89	87	85	89	87	86	84	87	86	84	83	81
				5.0	94	92	90	88	93	91	89	87	91	89	87	86	89	87	86	85	83
				7.0	95	94	92	91	94	93	91	90	92	91	90	89	90	89	88	87	85
				10.0	96	95	94	93	95	94	93	92	93	92	91	90	91	90	90	89	86

