

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 1
光源	NNU140105LE9 ×1 1130.0 lm
管理番号	K0132247 (1) DR 1
B Z 分類	BZ2

器具効率		94 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
上方光束		0 %		床	10 %				10 %				10 %				10 %				0 %
下方光束		94 %	室指数	照明率 (X0.01)																Z CM	
保守率		良 中 否	0.81	0.6	64	55	50	46	63	55	49	46	62	54	49	45	60	53	49	45	44
			0.77	0.8	73	65	60	56	72	65	60	56	70	64	59	56	68	63	59	55	54
			0.68	1.0	79	72	67	63	78	71	66	63	76	70	66	62	74	69	65	62	60
				1.25	83	77	72	69	82	76	72	68	80	75	71	68	78	74	70	68	66
下方投影面積		cm ²	1.5	86	81	76	73	85	80	76	73	83	78	75	72	81	77	74	71	70	
等価発光面積		cm ²	2.0	90	86	82	79	89	85	81	78	87	83	80	78	85	82	79	77	75	
取付 高さ	器具間隔最大限		2.5	92	89	85	83	91	88	85	82	89	86	83	81	87	84	82	80	78	
	横方向 (A) 縦方向 (B)		3.0	94	91	88	85	93	90	87	85	91	88	86	84	88	86	84	83	81	
H m	1.14 H m	1.14 H m	4.0	96	93	91	89	95	92	90	88	93	91	89	87	90	89	87	86	84	
			5.0	97	95	93	91	96	94	92	91	94	92	91	89	92	90	89	88	85	
			7.0	98	97	95	94	97	96	94	93	95	94	93	92	93	92	91	90	88	
			10.0	99	98	97	96	98	97	96	95	96	95	94	94	94	93	93	92	89	

