

| 屋内照明器具特性 |                             |
|----------|-----------------------------|
| 品番 (品名)  | NNN7 1 5 0 1                |
| 光源       | NNU141155LE9 ×1 1580.0 lm   |
| 管理番号     | K0133648 ( 0 ) DR 1         |
| BZ分類     | BZ2 / 0.7 / BZ1 / 0.9 / BZ2 |

| 器具効率     |                 | 96 %            | 反射率    | 天井              | 80 %              |     |    |     | 70 % |    |    |    | 50 % |    |    |    | 30 % |    |    |    | 0 % |
|----------|-----------------|-----------------|--------|-----------------|-------------------|-----|----|-----|------|----|----|----|------|----|----|----|------|----|----|----|-----|
|          |                 |                 |        | 壁               | 70                | 50  | 30 | 10  | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 70   | 50 | 30 | 10 | 0 % |
|          |                 |                 |        | 床               | 10 %              |     |    |     | 10 % |    |    |    | 10 % |    |    |    | 10 % |    |    |    | 0 % |
|          |                 |                 |        | 室指数             | 照明率 ( X0.01 ) ZCM |     |    |     |      |    |    |    |      |    |    |    |      |    |    |    |     |
| 保守率      |                 | 良<br>中<br>否     | 0.81   | 0.6             | 68                | 60  | 54 | 51  | 67   | 59 | 54 | 51 | 66   | 59 | 54 | 50 | 64   | 58 | 53 | 50 | 49  |
|          |                 |                 | 0.77   | 0.8             | 77                | 69  | 64 | 60  | 76   | 69 | 64 | 60 | 74   | 68 | 63 | 60 | 72   | 67 | 63 | 59 | 58  |
|          |                 |                 | 0.68   | 1.0             | 82                | 75  | 70 | 66  | 81   | 74 | 70 | 66 | 79   | 73 | 69 | 66 | 77   | 72 | 68 | 66 | 64  |
|          |                 |                 |        | 1.25            | 86                | 80  | 76 | 72  | 85   | 80 | 75 | 72 | 83   | 78 | 74 | 71 | 81   | 77 | 74 | 71 | 69  |
| 下方投影面積   |                 | cm <sup>2</sup> |        | 1.5             | 89                | 84  | 80 | 76  | 88   | 83 | 79 | 76 | 86   | 82 | 78 | 75 | 84   | 80 | 77 | 75 | 73  |
|          |                 |                 | 等価発光面積 | cm <sup>2</sup> | 2.0               | 93  | 88 | 85  | 82   | 92 | 88 | 84 | 81   | 89 | 86 | 83 | 81   | 87 | 84 | 82 | 80  |
| 取付<br>高さ | 器具間隔最大限         |                 | 2.5    | 95              | 91                | 88  | 85 | 94  | 90   | 87 | 85 | 92 | 89   | 86 | 84 | 89 | 87   | 85 | 83 | 81 |     |
|          | 横方向 (A) 縦方向 (B) |                 | 3.0    | 97              | 93                | 91  | 88 | 95  | 92   | 90 | 88 | 93 | 91   | 88 | 86 | 91 | 89   | 87 | 85 | 83 |     |
| H m      | 0.76 H m        | 0.76 H m        | 4.0    | 98              | 96                | 94  | 92 | 97  | 95   | 93 | 91 | 95 | 93   | 91 | 90 | 93 | 91   | 90 | 88 | 86 |     |
|          |                 |                 | 5.0    | 100             | 97                | 96  | 94 | 98  | 96   | 95 | 93 | 96 | 95   | 93 | 92 | 94 | 93   | 91 | 90 | 88 |     |
|          |                 |                 | 7.0    | 101             | 99                | 98  | 97 | 100 | 98   | 97 | 96 | 97 | 96   | 95 | 94 | 95 | 94   | 93 | 93 | 90 |     |
|          |                 |                 | 10.0   | 102             | 101               | 100 | 99 | 101 | 100  | 99 | 98 | 98 | 98   | 97 | 96 | 96 | 96   | 95 | 94 | 92 |     |

