

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 1
光源	NNU241105LE9 ×1 2010.0 lm
管理番号	K0133649 (0) DR 1
BZ分類	BZ2 / 0.7 / BZ1 / 0.9 / BZ2

器具効率		96 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		96 %	室指数	照明率 (X0.01) ZCM																		
保守率		良 中 否	0.81	0.6	68	60	54	51	67	59	54	51	66	59	54	50	64	58	53	50	49	
			0.77	0.8	77	69	64	60	76	69	64	60	74	68	63	60	72	67	63	59	58	
			0.68	1.0	82	75	70	66	81	74	70	66	79	73	69	66	77	72	68	66	64	
				1.25	86	80	76	72	85	80	75	72	83	78	74	71	81	77	74	71	69	
下方投影面積		cm ²	1.5	89	84	80	76	88	83	79	76	86	82	78	75	84	80	77	75	73		
等価発光面積		cm ²	2.0	93	88	85	82	92	88	84	81	89	86	83	81	87	84	82	80	78		
取付 高さ	器具間隔最大限		2.5	95	91	88	85	94	90	87	85	92	89	86	84	89	87	85	83	81		
	横方向 (A) 縦方向 (B)		3.0	97	93	91	88	95	92	90	88	93	91	88	86	91	89	87	85	83		
H m	0.76 H m	0.76 H m	4.0	98	96	94	92	97	95	93	91	95	93	91	90	93	91	90	88	86		
			5.0	100	97	96	94	98	96	95	93	96	95	93	92	94	93	91	90	88		
			7.0	101	99	98	97	100	98	97	96	97	96	95	94	95	94	93	93	90		
			10.0	102	101	100	99	101	100	99	98	98	98	97	96	96	96	95	94	92		

