

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 1
光源	NNU241105KLE9 ×1 2050.0 l m
管理番号	K0190797 (0) DB 1
B Z 分類	B Z 2

器具効率		91 %	反射率	天井	80 %				70 %				50 %				30 %				0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
				床	10 %				10 %				10 %				10 %				0 %	
上方光束 下方光束		0 % 91 %	室指数	照明率 (X0.01) Z C M																		
保守率		良 中 否	0.81	0.6	61	52	46	42	60	52	46	42	58	51	46	42	57	50	46	42	41	
			0.77	0.8	70	62	56	52	69	61	56	52	67	60	55	52	65	59	55	51	50	
			0.68	1.0	75	68	63	59	74	67	62	58	72	66	62	58	70	65	61	58	56	
				1.25	80	73	69	65	79	73	68	64	77	71	67	64	75	70	67	64	62	
下方投影面積 等価発光面積		cm ² cm ²		1.5	83	77	73	69	82	77	72	69	80	75	71	68	78	74	70	68	66	
			2.0	87	82	79	75	86	82	78	75	84	80	77	74	82	78	76	73	72		
取付 高さ	器具間隔最大限		2.5	90	86	82	79	88	85	82	79	86	83	80	78	84	81	79	77	75		
	横方向 (A) 縦方向 (B)		3.0	91	88	85	82	90	87	84	82	88	85	83	81	86	83	81	80	78		
H m	0.72 H m	0.72 H m	4.0	93	90	88	86	92	90	87	85	90	88	86	84	88	86	84	83	81		
			5.0	94	92	90	88	93	91	89	88	91	89	88	86	89	88	86	85	83		
			7.0	96	94	93	91	95	93	92	90	92	91	90	89	90	89	88	87	85		
			10.0	97	96	94	93	96	95	94	93	93	93	92	91	91	91	90	89	87		

