

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 1
光源	NNU140165KLE9 ×1 1450.0 lm
管理番号	K0190800 (0) DB 1
B Z 分類	BZ2

器具効率		93 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z CM
保守率		良 中 否	0.81	0.6	63	53	48	44	62	53	47	44	60	52	47	43	58	51	47	43	42
			0.77	0.8	72	64	58	54	71	63	58	54	69	62	58	54	67	61	57	54	52
			0.68	1.0	78	70	65	61	77	70	65	61	74	69	64	61	72	67	64	61	59
				1.25	82	76	71	68	81	75	71	67	79	74	70	67	77	73	69	66	65
下方投影面積		cm ²		1.5	85	80	75	72	84	79	75	72	82	77	74	71	80	76	73	70	69
			等価発光面積	cm ²	2.0	89	85	81	78	88	84	80	77	86	82	79	77	84	81	78	76
取付 高さ	器具間隔最大限			2.5	91	88	84	82	90	87	84	81	88	85	82	80	86	83	81	79	77
	横方向 (A)	縦方向 (B)		3.0	93	90	87	84	92	89	86	84	90	87	85	83	87	85	83	82	80
H m	1.20 H m	1.20 H m		4.0	95	92	90	88	94	91	89	87	92	90	88	86	89	88	86	85	83
				5.0	96	94	92	90	95	93	91	90	93	91	90	88	91	89	88	87	85
				7.0	97	96	94	93	96	95	93	92	94	93	92	91	92	91	90	89	87
				10.0	98	97	96	95	97	96	95	94	95	94	93	93	93	92	92	91	88

