

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 2
光源	NNU141155LE9 ×1 1580.0 lm
管理番号	K0133652 (0) DR 1
B Z 分類	BZ1 / 4.5 / BZ2 / 6.0 / BZ1

器具効率		83 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		83 %																						
保守率		良 中 否	0.81	0.6	64	57	53	50	63	57	53	50	62	56	53	50	60	56	52	50	49			
			0.77	0.8	70	64	60	57	69	63	60	57	67	63	59	57	66	62	59	56	55			
			0.68	1.0	73	68	64	62	73	68	64	61	71	67	64	61	69	66	63	61	60			
				1.25	77	72	68	66	76	71	68	65	74	70	67	65	72	69	67	65	63			
下方投影面積		cm ²	1.5	79	74	71	69	78	74	71	68	76	73	70	68	74	71	69	67	66				
等価発光面積		cm ²	2.0	81	78	75	73	80	77	75	72	79	76	74	72	77	75	73	71	69				
取付 高さ	器具間隔最大限		2.5	83	80	78	76	82	79	77	75	80	78	76	74	79	77	75	73	72				
	横方向 (A)		縦方向 (B)		3.0	84	82	80	78	83	81	79	77	81	79	78	76	80	78	77	75	73		
H m	0.78 H m		0.78 H m		4.0	86	84	82	80	85	83	81	80	83	81	80	79	81	80	79	78	76		
					5.0	87	85	83	82	86	84	83	81	84	82	81	80	82	81	80	79	77		
					7.0	88	86	85	84	87	85	84	83	85	84	83	82	83	82	81	81	79		
					10.0	88	87	87	86	87	87	86	85	85	85	84	84	84	83	83	82	80		

