

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 2
光源	NNU241105LE9 ×1 2010.0 lm
管理番号	K0133653 (0) DR 1
BZ分類	BZ1 / 4.5 / BZ2 / 6.0 / BZ1

器具効率		83 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.81	0.6	64	57	53	50	63	57	53	50	62	56	53	50	60	56	52	50	49
			0.77	0.8	70	64	60	57	69	63	60	57	67	63	59	57	66	62	59	56	55
			0.68	1.0	73	68	64	62	73	68	64	61	71	67	64	61	69	66	63	61	60
				1.25	77	72	68	66	76	71	68	65	74	70	67	65	72	69	67	65	63
下方投影面積 等価発光面積		cm ² cm ²		1.5	79	74	71	69	78	74	71	68	76	73	70	68	74	71	69	67	66
				2.0	81	78	75	73	80	77	75	72	79	76	74	72	77	75	73	71	69
取付 高さ	器具間隔最大限			2.5	83	80	78	76	82	79	77	75	80	78	76	74	79	77	75	73	72
	横方向 (A) 縦方向 (B)			3.0	84	82	80	78	83	81	79	77	81	79	78	76	80	78	77	75	73
H m	0.78 H m 0.78 H m			4.0	86	84	82	80	85	83	81	80	83	81	80	79	81	80	79	78	76
				5.0	87	85	83	82	86	84	83	81	84	82	81	80	82	81	80	79	77
				7.0	88	86	85	84	87	85	84	83	85	84	83	82	83	82	81	81	79
				10.0	88	87	87	86	87	87	86	85	85	85	84	84	84	83	83	82	80

