

屋内照明器具特性	
品番 (品名)	NNN71502
光源	NNU240105KLE9 x1 2050.0 lm
管理番号	K0190807 (0) DB 1
BZ分類	BZ1 / 1.8 / BZ2 / 8.5 / BZ1

器具効率		79 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.81	0.6	58	51	47	44	57	51	47	44	56	50	47	44	55	50	46	44	43
			0.77	0.8	64	58	54	51	63	58	54	51	62	57	53	51	60	56	53	51	49
			0.68	1.0	68	63	59	56	67	62	59	56	66	61	58	55	64	60	57	55	54
				1.25	72	67	63	60	71	66	63	60	69	65	62	60	67	64	61	59	58
下方投影面積		cm ²		1.5	74	69	66	63	73	69	66	63	71	68	65	62	69	66	64	62	61
			等価発光面積	cm ²	2.0	77	73	70	68	76	72	70	67	74	71	69	67	72	70	68	66
取付 高さ	器具間隔最大限			2.5	78	75	73	71	77	75	72	70	76	73	71	69	74	72	70	69	67
	横方向 (A) 縦方向 (B)			3.0	80	77	75	73	79	76	74	72	77	75	73	71	75	73	72	70	69
H m	1.17 H m	1.17 H m		4.0	81	79	77	76	80	78	77	75	78	77	75	74	77	75	74	73	71
				5.0	82	80	79	77	81	79	78	77	79	78	77	76	77	76	75	74	72
				7.0	83	82	81	80	82	81	80	79	80	79	78	78	79	78	77	76	74
				10.0	84	83	82	81	83	82	81	81	81	80	80	79	79	79	78	78	76

