

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 2
光源	NNU241105KLE9 ×1 2050.0 l m
管理番号	K0190809 (0) DB 1
B Z 分類	B Z 2

器具効率		79 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
上方光束 下方光束		79 %	室指数	照明率 (X0.01) Z C M																	
保守率		良 中 否	0.81	0.6	56	49	45	42	56	49	45	41	54	48	44	41	53	48	44	41	40
			0.77	0.8	63	57	52	49	62	56	52	49	61	55	51	49	59	54	51	48	47
			0.68	1.0	67	61	57	54	66	61	57	54	65	60	56	54	63	59	56	53	52
				1.25	71	66	62	59	70	65	61	58	68	64	61	58	66	63	60	58	56
下方投影面積		cm ²	1.5	73	69	65	62	72	68	65	62	70	67	64	61	69	66	63	61	59	
等価発光面積		cm ²	2.0	76	73	69	67	75	72	69	67	73	71	68	66	72	69	67	65	64	
取付 高さ	器具間隔最大限		2.5	78	75	72	70	77	74	72	70	75	73	71	69	74	72	70	68	66	
	横方向 (A) 縦方向 (B)		3.0	80	77	74	72	79	76	74	72	77	75	73	71	75	73	72	70	68	
H m	0.74 H m	0.74 H m	4.0	81	79	77	75	80	78	76	75	78	77	75	74	77	75	74	73	71	
			5.0	82	80	79	77	81	80	78	77	79	78	77	76	78	76	75	74	72	
			7.0	83	82	81	80	82	81	80	79	80	79	78	78	79	78	77	76	74	
			10.0	84	83	82	81	83	82	81	81	81	81	80	79	80	79	78	78	76	

