

# 屋内照明器具特性

品番 (品名)	L S E W2 0 0 5	
光源	LED2700_70_410 ×1	410.0 l m
管理番号	K0139579 ( 0 ) DB 1	
B Z 分類	B Z 6	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
	上方光束 19 %		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
下方光束	81 %	床		10 %				10 %				10 %				10 %				0 %
室指数	照明率 ( X0.01 )																			Z C M
保守率	良	0.63	0.6	51	38	30	24	48	37	29	24	44	34	28	23	40	32	26	22	18
	中	0.6	0.8	60	48	40	34	57	46	38	33	52	43	36	31	48	40	34	29	26
	否	0.56	1.0	66	55	47	40	63	53	45	39	58	49	42	37	53	45	40	35	31
			1.25	72	62	54	47	69	59	52	46	63	55	49	44	58	51	46	41	36
下方投影面積	c m <sup>2</sup>		1.5	76	67	59	53	73	64	57	51	67	59	53	49	61	55	50	46	40
	等価発光面積		c m <sup>2</sup>	2.0	82	74	67	61	79	71	65	59	72	66	61	56	66	61	57	53
取付高さ	器具間隔最大限		2.5	86	78	72	67	82	76	70	65	76	70	65	61	70	65	61	58	51
	横方向 ( A )	縦方向 ( B )	3.0	88	82	76	71	85	79	74	69	78	73	69	65	72	68	65	61	55
H m	1.39 H m	1.39 H m	4.0	92	86	82	77	88	83	79	75	82	78	74	71	75	72	69	66	59
			5.0	94	89	85	81	90	86	83	79	84	80	77	74	78	75	72	70	62
			7.0	96	93	90	87	93	90	87	84	86	84	81	79	80	78	76	74	66
			10.0	99	96	93	91	95	93	90	88	89	87	85	83	82	81	79	78	70

