

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 2
光源	NNU141155KLE9 x1 1610.0 l m
管理番号	K0190813 (0) DB 1
B Z 分類	BZ2

器具効率		80 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.81	0.6	57	50	45	42	56	49	45	42	54	49	45	42	53	48	44	42	41
			0.77	0.8	63	57	53	49	62	56	52	49	61	56	52	49	59	55	51	49	48
			0.68	1.0	68	62	58	54	67	61	57	54	65	60	57	54	63	59	56	54	52
				1.25	71	66	62	59	70	65	62	59	68	64	61	58	67	63	60	58	57
下方投影面積		c m ²	1.5	74	69	65	62	73	68	65	62	71	67	64	62	69	66	63	61	60	
			等価発光面積		c m ²	2.0	77	73	70	67	76	72	69	67	74	71	68	66	72	70	67
取付 高さ	器具間隔最大限		2.5	79	75	73	70	78	75	72	70	76	73	71	69	74	72	70	68	67	
	横方向 (A) 縦方向 (B)		3.0	80	77	75	73	79	76	74	72	77	75	73	71	75	73	72	70	69	
H m	0.74 H m	0.74 H m	4.0	81	79	77	76	80	78	77	75	79	77	75	74	77	75	74	73	71	
			5.0	82	81	79	78	81	80	78	77	80	78	77	76	78	77	76	75	73	
			7.0	83	82	81	80	83	81	80	79	81	80	79	78	79	78	77	77	74	
			10.0	84	83	83	82	83	83	82	81	82	81	80	79	80	79	79	78	76	

