

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 4
光源	NNU141155LE9 ×1 1580.0 l m
管理番号	K0133660 (0) DR 1
B Z 分類	BZ1

器具効率		88 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01)																				Z C M
保守率		良 中 否	0.81	0.6	67	60	56	53	66	60	56	53	65	59	55	52	63	58	55	52	51				
			0.77	0.8	74	67	63	60	73	67	63	60	71	66	63	60	70	65	62	60	58				
			0.68	1.0	78	72	68	65	77	72	68	65	75	71	67	65	73	70	67	64	63				
				1.25	81	76	73	70	80	76	72	69	78	74	71	69	77	73	71	69	67				
下方投影面積		c m ²		1.5	83	79	76	73	82	78	75	72	80	77	74	72	79	76	73	71	70				
			等価発光面積	c m ²	2.0	86	83	80	77	85	82	79	77	83	80	78	76	81	79	77	75	74			
取付 高さ	器具間隔最大限			2.5	88	85	82	80	87	84	82	80	85	83	81	79	83	81	79	78	76				
	横方向 (A)		縦方向 (B)	3.0	89	87	84	82	88	86	84	82	86	84	82	81	84	83	81	80	78				
H m	0.76 H m		0.76 H m	4.0	91	89	87	85	90	88	86	85	88	86	85	83	86	84	83	82	80				
				5.0	92	90	88	87	91	89	88	86	89	87	86	85	87	86	85	84	82				
				7.0	93	91	90	89	92	90	89	88	90	89	88	87	88	87	86	85	83				
				10.0	93	92	92	91	92	91	91	90	90	90	89	88	88	88	87	87	84				

