

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 4
光源	NNU240105KLE9 ×1 2050.0 l m
管理番号	K0190831 (0) DB 1
B Z 分類	BZ1 / 2.3 / BZ2

器具効率		85 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.81	0.6	62	55	50	47	61	54	50	47	59	53	49	46	58	53	49	46	45
			0.77	0.8	69	62	58	55	68	62	58	55	66	61	57	54	65	60	57	54	53
			0.68	1.0	73	67	63	60	72	67	63	60	71	66	62	60	69	65	62	59	58
				1.25	77	72	68	65	76	71	67	65	74	70	67	64	72	69	66	64	62
下方投影面積		cm ²		1.5	79	75	71	68	78	74	71	68	76	73	70	67	75	72	69	67	65
			等価発光面積	cm ²	2.0	82	79	75	73	81	78	75	73	79	76	74	72	78	75	73	71
取付 高さ	器具間隔最大限			2.5	84	81	78	76	83	80	78	76	81	79	77	75	79	77	76	74	72
	横方向 (A)		縦方向 (B)	3.0	86	83	80	78	84	82	80	78	83	80	78	77	81	79	77	76	74
H m	1.07 H m		1.07 H m	4.0	87	85	83	81	86	84	82	81	84	82	81	80	82	81	80	78	76
				5.0	88	86	85	83	87	85	84	83	85	84	82	81	83	82	81	80	78
				7.0	89	88	87	85	88	87	86	85	86	85	84	83	84	83	83	82	80
				10.0	90	89	88	87	89	88	87	86	87	86	86	85	85	85	84	83	81

