

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 4
光源	NNU241105KLE9 x1 2050.0 l m
管理番号	K0190833 (0) DB 1
B Z 分類	BZ2

器具効率		84 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																			Z C M	
下方光束		84 %																						
保守率		良 中 否	0.81	0.6	60	52	47	44	59	52	47	44	57	51	47	44	56	50	47	44	43			
			0.77	0.8	67	60	56	52	66	60	55	52	64	59	55	52	63	58	54	52	50			
			0.68	1.0	72	65	61	58	71	65	61	57	69	64	60	57	67	63	59	57	55			
				1.25	75	70	66	63	74	69	65	62	72	68	65	62	71	67	64	62	60			
下方投影面積		c m ²		1.5	78	73	69	66	77	72	69	66	75	71	68	65	73	70	67	65	63			
等価発光面積			c m ²	2.0	81	77	74	71	80	76	73	71	78	75	72	70	76	74	71	70	68			
				2.5	83	80	77	75	82	79	76	74	80	78	75	73	78	76	74	73	71			
取付 高さ	器具間隔最大限		3.0	84	82	79	77	83	81	78	76	81	79	77	76	80	78	76	75	73				
	横方向 (A)			縦方向 (B)		4.0	86	84	82	80	85	83	81	80	83	81	80	78	81	80	79	77		
H m	0.72 H m		0.72 H m		5.0	87	85	84	82	86	84	83	81	84	83	81	80	82	81	80	79	77		
					7.0	88	87	86	84	87	86	85	84	85	84	83	82	83	83	82	81	79		
					10.0	89	88	87	86	88	87	86	86	86	85	85	84	84	84	83	83	80		

