

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 4
光源	NNU141165KLE9 ×1 1450.0 l m
管理番号	K0190838 (0) DB 1
B Z 分類	BZ2

器具効率		84 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.81	0.6	60	52	48	44	59	52	47	44	58	51	47	44	56	51	47	44	43
			0.77	0.8	67	60	56	52	66	60	56	52	65	59	55	52	63	58	55	52	51
			0.68	1.0	72	66	61	58	71	65	61	58	69	64	60	57	67	63	60	57	56
				1.25	75	70	66	63	74	69	66	63	72	68	65	62	71	67	64	62	60
下方投影面積		c m ²		1.5	78	73	69	66	77	73	69	66	75	71	68	66	73	70	67	65	64
				2.0	81	77	74	71	80	77	74	71	78	75	73	70	76	74	72	70	68
取付	器具間隔最大限			2.5	83	80	77	75	82	79	77	74	80	78	75	73	78	76	74	73	71
高さ	横方向 (A)		縦方向 (B)	3.0	85	82	79	77	84	81	79	77	82	79	77	76	80	78	76	75	73
H m	0.72 H m		0.72 H m	4.0	86	84	82	80	85	83	81	80	83	81	80	79	81	80	79	77	75
				5.0	87	85	84	82	86	85	83	82	84	83	82	80	82	81	80	79	77
				7.0	88	87	86	85	87	86	85	84	85	84	83	82	84	83	82	81	79
				10.0	89	88	87	86	88	87	86	86	86	86	85	84	84	84	83	83	80

