

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 4
光源	NNU140105KLE9 ×1 1130.0 l m
管理番号	K0190839 (0) DB 1
B Z 分類	BZ1 / 1.8 / BZ2

器具効率		85 %	反射率	天井	80 %				70 %				50 %				30 %				0 %			
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				床	10 %				10 %				10 %				10 %				0 %			
上方光束		0 %	室指数	照明率 (X0.01)																		Z	C	M
下方光束		85 %																						
保守率		良 中 否	0.81	0.6	61	54	49	46	60	54	49	46	59	53	49	46	58	52	49	46	45			
			0.77	0.8	68	62	57	54	68	61	57	54	66	61	57	54	64	60	56	54	52			
			0.68	1.0	73	67	63	60	72	66	62	59	70	65	62	59	68	64	61	59	57			
				1.25	76	71	67	64	75	71	67	64	74	70	66	64	72	68	66	63	62			
下方投影面積		c m ²		1.5	79	74	71	68	78	74	70	67	76	72	69	67	74	71	69	66	65			
等価発光面積			c m ²	2.0	82	78	75	72	81	77	75	72	79	76	74	71	77	75	73	71	69			
取付 高さ	器具間隔最大限		2.5	84	81	78	76	83	80	77	75	81	78	76	74	79	77	75	73	72				
	横方向 (A)		縦方向 (B)	3.0	85	82	80	78	84	82	79	77	82	80	78	76	80	78	77	75	74			
H m	1.09 H m	1.09 H m	4.0	87	85	83	81	86	84	82	80	84	82	80	79	82	80	79	78	76				
			5.0	88	86	84	83	87	85	83	82	85	83	82	81	83	82	81	80	78				
			7.0	89	87	86	85	88	87	85	84	86	85	84	83	84	83	82	82	79				
			10.0	90	89	88	87	89	88	87	86	87	86	85	84	85	84	84	83	81				

