

屋内照明器具特性	
品番 (品名)	NNN7 1 5 0 4
光源	NNU141105KLE9 ×1 1130.0 l m
管理番号	K0190841 (0) DB 1
B Z 分類	BZ2

器具効率		84 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.81	0.6	60	52	47	44	59	52	47	44	57	51	47	44	56	50	46	44	42
			0.77	0.8	67	60	55	52	66	60	55	52	64	59	55	52	63	58	54	52	50
			0.68	1.0	71	65	61	57	70	65	60	57	68	64	60	57	67	63	59	57	55
				1.25	75	70	66	62	74	69	65	62	72	68	64	62	70	67	64	61	60
下方投影面積		c m ²		1.5	78	73	69	66	77	72	69	66	75	71	68	65	73	70	67	65	63
				2.0	81	77	74	71	80	76	73	71	78	75	72	70	76	73	71	69	68
取付	器具間隔最大限			2.5	83	80	77	74	82	79	76	74	80	77	75	73	78	76	74	72	71
高さ	横方向 (A)		縦方向 (B)	3.0	84	81	79	77	83	81	78	76	81	79	77	75	79	77	76	74	72
H m	0.72 H m	0.72 H m	4.0	86	84	82	80	85	83	81	79	83	81	80	78	81	80	78	77	75	
			5.0	87	85	83	82	86	84	83	81	84	82	81	80	82	81	80	79	77	
			7.0	88	87	85	84	87	86	85	84	85	84	83	82	83	82	82	81	79	
			10.0	89	88	87	86	88	87	86	85	86	85	84	84	84	83	83	82	80	

