

屋内照明器具特性

品番 (品名)	LGB84396									
光源	LED2700_70_876 x1					876.0 l m				
管理番号	K0135904(0)DB1									
BZ分類	BZ3									

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	0%	床	10%				10%				10%				10%				0%	
下方光束	100%	室指数	照明率 (X0.01)																ZCM	
保守率	良 中 否 0.67 0.63 0.56	0.6	63	52	45	40	62	51	45	40	59	50	44	40	57	49	44	40	38	
		0.8	73	64	57	52	72	63	57	52	70	62	56	52	68	61	56	52	50	
		1.0	80	72	65	61	79	71	65	60	76	69	64	60	74	68	63	60	58	
		1.25	86	78	72	68	84	77	72	68	82	76	71	67	79	74	70	67	65	
下方投影面積	c m ²	1.5	89	82	77	73	88	82	77	73	85	80	76	72	83	78	75	71	69	
		2.0	94	88	84	80	92	87	83	80	90	86	82	79	87	84	81	78	76	
取付高さ	器具間隔最大限		2.5	97	92	88	85	95	91	87	84	93	89	86	83	90	87	85	80	
	横方向 (A)	縦方向 (B)	3.0	99	94	91	88	97	93	90	87	95	92	89	86	92	90	87	85	83
H m	1.27 H m	1.27 H m	4.0	101	98	95	92	100	97	94	92	97	95	92	90	95	93	91	89	87
			5.0	102	100	97	95	101	99	96	94	99	97	95	93	96	95	93	92	89
			7.0	104	102	100	99	103	101	99	98	100	99	97	96	98	97	96	94	92
			10.0	105	104	102	101	104	103	101	100	101	100	99	98	99	98	98	97	94

