

屋内照明器具特性	
品番 (品名)	LGB52111
光源	LED2700_70_2125 ×1 2125.0 lm
管理番号	K0143783 (0) DB1
BZ分類	BZ5

器具効率		100 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z
保守率		良 中 否	0.69	0.6	54	42	34	28	52	41	33	28	49	39	32	27	46	37	31	27	24
			0.67	0.8	64	52	44	38	62	51	43	38	58	48	42	37	54	46	40	36	33
			0.63	1.0	70	59	51	45	68	58	50	44	64	55	48	43	60	53	47	42	39
			0.63	1.25	76	66	58	52	74	64	57	51	69	61	55	50	65	59	53	49	45
下方投影面積		cm ²	1.5	80	71	63	58	78	69	62	57	73	66	60	55	69	63	58	54	50	
			等価発光面積		cm ²	2.0	86	78	71	66	83	76	70	65	79	72	67	63	74	69	65
取付 高さ	器具間隔最大限		2.5	89	82	76	71	87	80	75	70	82	77	72	68	78	73	69	66	62	
	横方向 (A)	縦方向 (B)	3.0	92	86	80	76	89	84	79	74	85	80	76	72	80	76	73	70	65	
1.5m	2.02 m	2.12 m	4.0	95	90	86	82	93	88	84	80	88	84	81	78	84	81	78	75	70	
2	2.66	2.67	5.0	97	93	89	86	95	91	87	84	90	87	84	81	86	83	81	78	74	
2.5	3.31	3.24	7.0	99	96	93	90	97	94	91	89	93	90	88	86	88	86	85	83	78	
3	3.96	3.83	10.0	101	99	97	95	99	97	95	93	95	93	91	89	91	89	88	86	81	

