

屋内照明器具特性	
品番 (品名)	LGB85030
光源	LED5000_70_1100 x1 1100.0 lm
管理番号	K0138505 (1) DB 1
BZ分類	BZ6/0.7/BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	17%	床	10%				10%				10%				10%				0%	
下方光束	83%	室指数	照明率 ( X0.01 )																ZCM	
保守率	良	0.63	0.6	5.2	4.0	3.2	2.6	5.0	3.9	3.1	2.6	4.6	3.6	3.0	2.5	4.2	3.4	2.8	2.4	2.1
	中	0.6	0.8	6.2	5.0	4.2	3.6	5.9	4.8	4.1	3.5	5.4	4.5	3.8	3.4	5.0	4.2	3.6	3.2	2.8
	否	0.56	1.0	6.8	5.7	4.9	4.3	6.5	5.5	4.7	4.2	6.0	5.1	4.5	4.0	5.5	4.8	4.3	3.8	3.4
			1.25	7.4	6.4	5.6	5.0	7.1	6.1	5.4	4.9	6.5	5.7	5.1	4.6	6.0	5.4	4.9	4.4	4.0
下方投影面積			1.5	7.8	6.8	6.1	5.5	7.5	6.6	5.9	5.4	6.9	6.2	5.6	5.1	6.4	5.8	5.3	4.9	4.4
			2.0	8.4	7.6	6.9	6.3	8.0	7.3	6.7	6.2	7.4	6.8	6.3	5.9	6.9	6.4	6.0	5.6	5.0
取付高さ	器具間隔最大限		2.5	8.7	8.0	7.4	6.9	8.4	7.8	7.2	6.7	7.8	7.3	6.8	6.4	7.2	6.8	6.4	6.1	5.5
	横方向 (A)	縦方向 (B)	3.0	9.0	8.4	7.8	7.4	8.7	8.1	7.6	7.2	8.0	7.6	7.2	6.8	7.5	7.1	6.8	6.4	5.8
1.5m	2.12m	1.88m	4.0	9.3	8.8	8.4	8.0	9.0	8.5	8.1	7.7	8.4	8.0	7.7	7.3	7.8	7.5	7.2	6.9	6.3
2	2.82	2.48	5.0	9.5	9.1	8.7	8.3	9.2	8.8	8.5	8.1	8.6	8.3	8.0	7.7	8.0	7.7	7.5	7.3	6.6
2.5	3.54	3.08	7.0	9.8	9.4	9.1	8.8	9.4	9.1	8.9	8.6	8.8	8.6	8.4	8.1	8.3	8.1	7.9	7.7	7.0
3	4.2	3.66	10.0	9.9	9.7	9.5	9.3	9.6	9.4	9.2	9.0	9.0	8.8	8.7	8.5	8.5	8.3	8.2	8.0	7.3

