

屋内照明器具特性

品番 (品名)	LGBZ7201															
光源	LED6500_70_3700 x1 3700.0 lm															
管理番号	K0127302(0)DB1															
BZ分類	BZ6/0.7/BZ5															

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	12%	反射率	床	10%				10%				10%				10%				0%
下方光束	88%		室指数	照明率 (X0.01) ZCM																
保守率	良 中 否	0.63	0.6	53	41	33	27	51	40	32	27	48	38	31	26	44	36	30	25	23
		0.6	0.8	63	51	43	37	60	49	42	36	56	47	40	35	52	44	39	34	31
			1.0	69	58	50	44	67	56	49	43	62	53	47	42	58	50	45	40	37
		0.56	1.25	75	65	57	51	72	63	56	50	67	59	53	48	63	56	51	46	42
下方投影面積	c m ²	1.5	79	69	62	56	76	68	61	55	71	64	58	53	67	60	55	51	47	
		2.0	85	76	70	64	82	74	68	63	77	70	65	61	72	67	62	58	54	
取付高さ	器具間隔最大限		2.5	88	81	75	70	85	79	73	69	80	75	70	66	75	71	67	63	58
	横方向 (A)	縦方向 (B)	3.0	91	84	79	74	88	82	77	73	83	78	74	70	78	74	70	67	62
1.5m	1.94 m	1.93 m	4.0	94	89	84	80	91	87	82	79	86	82	79	75	81	78	75	72	67
2	2.55	2.54	5.0	96	92	88	84	93	89	86	83	88	85	82	79	83	81	78	76	70
2.5	3.17	3.16	7.0	99	95	92	89	96	93	90	87	91	88	86	84	86	84	82	80	74
3	3.8	3.79	10.0	100	98	96	93	98	96	93	91	93	91	89	87	88	86	85	83	77

