

屋内照明器具特性

品番 (品名)	XLGE7122									
光源	LED2700_70_215 x1 215.0 lm									
管理番号	K0147858 (0) DB 1									
B Z 分類	BZ4									

器具効率		1 0 0 %	反射率	天井	8 0 %					7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %		
				床	1 0 %					1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		3 2 % 6 8 %	室指数	照明率 (X 0 . 0 1) Z C M																			
保守率		良 中 否	0 . 6	5 5	4 4	3 7	3 2	5 2	4 2	3 6	3 1	4 7	3 9	3 3	2 9	4 2	3 5	3 1	2 7	2 3			
			0 . 6	6 4	5 4	4 7	4 2	6 1	5 1	4 5	4 0	5 5	4 7	4 2	3 8	4 9	4 3	3 9	3 5	3 0			
			1 . 0	7 0	6 1	5 4	4 9	6 7	5 8	5 2	4 7	6 0	5 3	4 8	4 4	5 4	4 8	4 4	4 1	3 5			
			0 . 5 6	1 . 2 5	7 6	6 7	6 1	5 6	7 2	6 4	5 8	5 4	6 5	5 9	5 4	5 0	5 8	5 3	4 9	4 6	4 0		
下方投影面積		c m ²	1 . 5	8 0	7 2	6 6	6 1	7 6	6 9	6 3	5 9	6 8	6 3	5 8	5 5	6 1	5 7	5 3	5 0	4 3			
等価発光面積		c m ²	2 . 0	8 5	7 8	7 3	6 9	8 0	7 5	7 0	6 6	7 2	6 8	6 4	6 1	6 5	6 2	5 9	5 6	4 8			
取付 高さ	器具間隔最大限		2 . 5	8 8	8 2	7 8	7 4	8 4	7 9	7 5	7 1	7 5	7 2	6 8	6 5	6 8	6 5	6 2	6 0	5 2			
	横方向 (A)	縦方向 (B)	3 . 0	9 0	8 5	8 1	7 8	8 6	8 1	7 8	7 5	7 7	7 4	7 1	6 9	6 9	6 7	6 5	6 3	5 4			
H m	0 . 0 0 H m	0 . 0 0 H m	4 . 0	9 3	8 9	8 6	8 3	8 8	8 5	8 2	7 9	8 0	7 7	7 5	7 3	7 2	7 0	6 8	6 6	5 7			
			5 . 0	9 4	9 1	8 8	8 6	9 0	8 7	8 5	8 2	8 1	7 9	7 7	7 5	7 3	7 2	7 0	6 9	5 9			
			7 . 0	9 6	9 4	9 2	9 0	9 2	9 0	8 8	8 6	8 3	8 2	8 0	7 9	7 5	7 4	7 3	7 2	6 1			
			1 0 . 0	9 8	9 6	9 4	9 3	9 3	9 2	9 0	8 9	8 4	8 3	8 2	8 1	7 6	7 5	7 5	7 4	6 3			

