

屋内照明器具特性	
品番 (品名)	L G B 5 1 6 1 5
光源	LED2700_70_820 ×1 820.0 lm
管理番号	K0147632 (0) DB 1
B Z 分類	B Z 5

器具効率		1 0 0 % 上方光束 2 0 % 下方光束 8 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
			室指数	照明率 (X 0 . 0 1) Z C M																	
保守率		良 中 否	0 . 6 3	0 . 6	5 3	4 1	3 3	2 8	5 1	4 0	3 3	2 8	4 6	3 7	3 1	2 6	4 3	3 5	2 9	2 5	2 2
			0 . 6	0 . 8	6 3	5 1	4 3	3 8	6 0	4 9	4 2	3 7	5 5	4 6	4 0	3 5	5 0	4 3	3 8	3 3	3 0
			0 . 5 6	1 . 0	6 9	5 8	5 1	4 5	6 6	5 6	4 9	4 4	6 1	5 2	4 6	4 2	5 5	4 9	4 4	4 0	3 5
				1 . 2 5	7 5	6 5	5 8	5 2	7 2	6 3	5 6	5 1	6 6	5 8	5 3	4 8	6 0	5 4	5 0	4 6	4 1
下方投影面積		c m ²	1 . 5	7 9	7 0	6 3	5 7	7 6	6 7	6 1	5 6	6 9	6 3	5 7	5 3	6 4	5 8	5 4	5 0	4 5	
等価発光面積			c m ²	2 . 0	8 4	7 7	7 1	6 5	8 1	7 4	6 8	6 4	7 5	6 9	6 4	6 0	6 9	6 4	6 0	5 7	5 1
取付 高さ	器具間隔最大限		2 . 5	8 8	8 1	7 6	7 1	8 4	7 8	7 3	6 9	7 8	7 3	6 9	6 5	7 2	6 8	6 4	6 1	5 5	
	横方向 (A) 縦方向 (B)		3 . 0	9 0	8 4	7 9	7 5	8 7	8 2	7 7	7 3	8 0	7 6	7 2	6 9	7 4	7 1	6 8	6 5	5 8	
H m	1 . 2 9 H m	1 . 2 9 H m	4 . 0	9 3	8 9	8 5	8 1	9 0	8 6	8 2	7 9	8 3	8 0	7 7	7 4	7 7	7 4	7 2	7 0	6 2	
			5 . 0	9 5	9 1	8 8	8 5	9 2	8 8	8 5	8 2	8 5	8 2	8 0	7 7	7 9	7 7	7 5	7 3	6 5	
			7 . 0	9 8	9 5	9 2	8 9	9 4	9 1	8 9	8 7	8 7	8 5	8 3	8 1	8 1	7 9	7 8	7 6	6 8	
			1 0 . 0	9 9	9 7	9 5	9 3	9 6	9 4	9 2	9 0	8 9	8 8	8 6	8 5	8 3	8 2	8 0	7 9	7 1	

