

屋内照明器具特性	
品番 (品名)	NNN6 1 5 2 3 W
光源	LDA7 L - H / S / 6 × 1 810.0 l m
管理番号	K0178373 (0) DB 1
B Z 分類	B Z 3

器具効率		64 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) Z C M																
保守率		良 中 否	0.67	0.6	41	34	30	27	40	34	30	27	39	33	30	27	38	33	29	27	26
			0.63	0.8	48	41	37	34	47	41	37	34	45	40	37	34	44	39	36	34	33
			0.56	1.0	52	46	42	39	51	46	42	39	49	45	41	39	48	44	41	38	37
				1.25	55	50	46	44	54	50	46	43	53	49	46	43	51	48	45	43	41
下方投影面積		cm ²		1.5	57	53	49	47	57	52	49	47	55	51	48	46	53	50	48	46	44
			等価発光面積	cm ²	2.0	60	57	54	51	60	56	53	51	58	55	53	51	56	54	52	50
取付 高さ	器具間隔最大限			2.5	62	59	57	54	61	59	56	54	60	57	55	53	58	56	54	53	51
	横方向 (A) 縦方向 (B)			3.0	63	61	59	57	63	60	58	56	61	59	57	55	59	58	56	55	53
H m	1.28 H m	1.28 H m		4.0	65	63	61	59	64	62	61	59	63	61	59	58	61	60	58	57	56
				5.0	66	64	63	61	65	64	62	61	64	62	61	60	62	61	60	59	57
				7.0	67	66	65	63	66	65	64	63	65	64	63	62	63	62	62	61	59
				10.0	68	67	66	65	67	66	65	65	65	65	64	63	64	63	63	62	61

