

屋内照明器具特性	
品番 (品名)	NNN6 1 5 2 3 W
光源	LDA4 L - G/ K4 ×1 485.0 l m
管理番号	K0178376 (0) DB 1
B Z 分類	BZ3

器具効率		61 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z C M
保守率		良 中 否	0.67	0.6	38	32	27	24	38	31	27	24	36	31	27	24	35	30	27	24	23
			0.63	0.8	45	39	34	31	44	38	34	31	42	37	34	31	41	37	34	31	30
			0.56	1.0	49	43	39	36	48	43	39	36	46	42	38	36	45	41	38	36	35
				1.25	52	47	44	41	51	47	43	41	50	46	43	40	48	45	42	40	39
下方投影面積		c m ²		1.5	54	50	46	44	53	49	46	44	52	48	46	43	50	47	45	43	42
				2.0	57	54	51	48	56	53	50	48	55	52	50	48	53	51	49	47	46
取付 高さ	器具間隔最大限			2.5	59	56	53	51	58	55	53	51	57	54	52	50	55	53	51	50	48
	横方向 (A)		縦方向 (B)	3.0	60	58	55	53	59	57	55	53	58	56	54	52	56	55	53	52	50
H m	1.31 H m	1.31 H m		4.0	62	60	58	56	61	59	57	56	59	58	56	55	58	57	55	54	53
				5.0	63	61	59	58	62	60	59	58	60	59	58	57	59	58	57	56	54
				7.0	64	62	61	60	63	62	61	60	61	60	60	59	60	59	58	58	56
				10.0	64	64	63	62	64	63	62	61	62	62	61	60	61	60	60	59	57

