

屋内照明器具特性	
品番 (品名)	NNN6 1 5 2 3 W
光源	LDA7 L - G / D / S / K6 ×1 810.0 lm
管理番号	K0167256 (0) DB 1
B Z 分類	BZ3

器具効率		56 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																ZCM
保守率		良 中 否	0.67	0.6	35	29	25	22	34	29	25	22	33	28	25	22	32	28	25	22	21
			0.63	0.8	41	35	32	29	40	35	31	29	39	34	31	29	38	34	31	29	28
			0.56	1.0	45	40	36	33	44	39	36	33	42	38	35	33	41	38	35	33	32
				1.25	48	43	40	37	47	43	40	37	45	42	39	37	44	41	39	37	36
下方投影面積		cm ²		1.5	50	46	43	40	49	45	42	40	47	44	42	40	46	43	41	39	38
			等価発光面積	cm ²	2.0	52	49	46	44	52	49	46	44	50	48	45	44	49	47	45	43
取付 高さ	器具間隔最大限			2.5	54	51	49	47	53	51	49	47	52	50	48	46	50	49	47	46	44
	横方向 (A) 縦方向 (B)			3.0	55	53	51	49	54	52	50	49	53	51	49	48	51	50	49	47	46
H m	1.29 H m	1.29 H m		4.0	56	55	53	51	56	54	52	51	54	53	52	50	53	52	51	50	48
				5.0	57	56	54	53	57	55	54	53	55	54	53	52	54	53	52	51	50
				7.0	58	57	56	55	57	56	56	55	56	55	54	54	55	54	53	53	51
				10.0	59	58	57	57	58	57	57	56	57	56	56	55	56	55	55	54	53

