

屋内照明器具特性	
品番 (品名)	NNN6 1 5 2 3 B
光源	LDA4 L - G/ K4 ×1 485.0 lm
管理番号	K0178372 (0) DB 1
B Z 分類	BZ1

器具効率		30 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01) ZCM																
保守率		良 中 否	0.67	0.6	21	19	17	16	21	18	17	16	20	18	17	16	20	18	17	16	15
			0.63	0.8	24	22	20	19	24	22	20	19	23	21	20	19	23	21	20	19	18
			0.56	1.0	26	24	22	21	26	24	22	21	25	23	22	21	24	23	22	21	21
			1.25	27	26	24	23	27	25	24	23	26	25	24	23	26	25	24	23	22	
下方投影面積		cm ²	1.5	28	27	25	24	28	26	25	24	27	26	25	24	27	26	25	24	23	
			2.0	29	28	27	26	29	28	27	26	28	27	26	26	28	27	26	26	25	
等価発光面積		cm ²	2.5	30	29	28	27	30	29	28	27	29	28	27	27	28	28	27	27	26	
			3.0	30	29	29	28	30	29	28	28	29	29	28	28	29	28	28	27	27	
H m	1.18 H m	1.18 H m	4.0	31	30	30	29	31	30	29	29	30	29	29	28	29	29	28	28	27	
			5.0	31	31	30	30	31	30	30	29	30	30	29	29	30	29	29	29	28	
			7.0	32	31	31	30	31	31	30	30	31	30	30	30	30	30	29	29	28	
			10.0	32	32	31	31	31	31	31	31	31	31	30	30	30	30	30	30	29	

