

屋内照明器具特性

品番 (品名)	L G W 8 0 2 3 5	
光源	LED2700_70_335 x1	335.0 l m
管理番号	K0135012 (0) DB 1	
B Z 分類	B Z 5	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	4 %	床	10 %				10 %				10 %				10 %				0 %	
下方光束	96 %	室指数	照明率 (X0.01)																Z C M	
保守率	良	0.63	0.6	5.6	4.4	3.6	3.0	5.5	4.3	3.6	3.0	5.2	4.2	3.5	3.0	4.9	4.0	3.4	3.0	2.7
	中	0.6	0.8	6.6	5.5	4.7	4.1	6.5	5.4	4.7	4.1	6.2	5.2	4.6	4.1	5.9	5.1	4.5	4.0	3.8
	否	0.56	1.0	7.3	6.3	5.5	4.9	7.1	6.2	5.4	4.9	6.8	6.0	5.3	4.8	6.5	5.8	5.2	4.8	4.5
			1.25	7.9	7.0	6.3	5.7	7.7	6.9	6.2	5.7	7.4	6.6	6.0	5.6	7.1	6.4	5.9	5.5	5.2
下方投影面積		cm ²	1.5	8.3	7.5	6.8	6.3	8.2	7.3	6.7	6.2	7.8	7.1	6.6	6.1	7.5	6.9	6.4	6.0	5.7
等価発光面積		cm ²	2.0	8.9	8.2	7.6	7.1	8.7	8.0	7.5	7.0	8.3	7.8	7.3	6.9	8.0	7.5	7.1	6.8	6.5
取付高さ	器具間隔最大限		2.5	9.2	8.6	8.1	7.6	9.0	8.5	8.0	7.6	8.7	8.2	7.8	7.4	8.4	8.0	7.6	7.3	7.0
	横方向 (A)	縦方向 (B)	3.0	9.5	8.9	8.5	8.1	9.3	8.8	8.4	8.0	8.9	8.5	8.1	7.8	8.6	8.3	7.9	7.7	7.3
H m	1.42 H m	1.42 H m	4.0	9.8	9.3	9.0	8.6	9.6	9.2	8.8	8.5	9.2	8.9	8.6	8.3	8.9	8.6	8.4	8.1	7.8
			5.0	10.0	9.6	9.3	9.0	9.8	9.4	9.1	8.9	9.4	9.2	8.9	8.7	9.1	8.9	8.7	8.5	8.1
			7.0	10.2	9.9	9.6	9.4	10.0	9.7	9.5	9.3	9.7	9.4	9.3	9.1	9.3	9.2	9.0	8.8	8.5
			10.0	10.3	10.1	9.9	9.8	10.2	10.0	9.8	9.6	9.8	9.7	9.5	9.4	9.5	9.4	9.3	9.2	8.8

