

屋内照明器具特性

品番 (品名)	L G W 8 1 5 1 1									
光源	LED2700_70_345 ×1					345.0 l m				
管理番号	K0142279 (0) DB 1									
B Z 分類	B Z 3									

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %																																				
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %																																				
		床	10 %				10 %				10 %				10 %				0 %																																				
上方光束	50 %	室指数																		照明率 (X 0.01)																		Z C M																	
下方光束	50 %																																																						
保守率	良 中 否	0.63	0.6	0.56	0.6	54	43	37	32	50	41	35	31	43	36	31	28	37	31	28	25	20																																	
		0.6	0.6	0.6	0.6	63	53	46	41	58	50	44	39	50	44	39	36	43	38	34	32	25																																	
		0.56	0.56	0.56	0.56	69	60	53	48	64	56	50	46	55	49	45	41	47	42	39	37	29																																	
		0.56	0.56	0.56	0.56	74	66	60	55	69	62	56	52	59	54	50	46	50	46	43	41	32																																	
下方投影面積	c m ²	1.25	1.5	2.0	2.5	85	80	75	72	79	75	71	68	68	65	62	60	58	55	53	52	40																																	
		1.5	2.0	2.5	3.0	87	82	79	75	81	77	74	71	70	67	64	62	59	57	55	54	41																																	
等価発光面積	c m ²	2.0	2.5	3.0	4.0	89	86	83	80	83	80	78	75	72	70	68	66	61	59	58	57	43																																	
		2.5	3.0	4.0	5.0	91	88	85	83	85	82	80	78	73	71	70	68	62	61	59	58	44																																	
取付高さ	器具間隔最大限		H m	1.10 H m	1.22 H m	7.0	93	91	89	87	87	85	83	81	75	73	72	71	63	62	61	61	46																																
	10.0	94				93	91	90	88	87	85	84	76	75	74	73	64	63	63	62	47																																		

