

屋内照明器具特性

品番 (品名)	L G W8 1 5 1 3				
光源	LED2700_70_245 x1 245.0 l m				
管理番号	K0142279 (0) DB 1				
B Z 分類	B Z 3				

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
	上方光束		50 %	壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
	下方光束		50 %		床	10 %				10 %				10 %				10 %			
室指数	照明率 (X0.01)																				Z C M
保守率	良	0.63	0.6	54	43	37	32	50	41	35	31	43	36	31	28	37	31	28	25	20	
	中	0.6	0.8	63	53	46	41	58	50	44	39	50	44	39	36	43	38	34	32	25	
	否	0.56	1.0	69	60	53	48	64	56	50	46	55	49	45	41	47	42	39	37	29	
			1.25	74	66	60	55	69	62	56	52	59	54	50	46	50	46	43	41	32	
下方投影面積 等価発光面積	c m ²		1.5	77	70	64	60	72	66	61	57	62	57	53	50	52	49	46	44	35	
	c m ²		2.0	82	76	71	67	76	71	67	63	66	62	59	56	56	53	51	49	38	
	器具間隔最大限		2.5	85	80	75	72	79	75	71	68	68	65	62	60	58	55	53	52	40	
取付高さ	H m		3.0	87	82	79	75	81	77	74	71	70	67	64	62	59	57	55	54	41	
	1.10 H m	1.22 H m	4.0	89	86	83	80	83	80	78	75	72	70	68	66	61	59	58	57	43	
			5.0	91	88	85	83	85	82	80	78	73	71	70	68	62	61	59	58	44	
			7.0	93	91	89	87	87	85	83	81	75	73	72	71	63	62	61	61	46	
			10.0	94	93	91	90	88	87	85	84	76	75	74	73	64	63	63	62	47	

