

屋内照明器具特性	
品番 (品名)	L G B 5 1 6 5 2
光源	LED3500_70_443 ×1 443.0 lm
管理番号	K0142041 (2) DB 1
B Z 分類	B Z 5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %	
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %	
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %	
上方光束 下方光束		1 0 0 %	室指数	照明率 (X 0 . 0 1) Z C M																		
保守率		良 中 否	0 . 6 9	0 . 6	5 7	4 4	3 6	3 1	5 5	4 4	3 6	3 1	5 3	4 3	3 6	3 1	5 1	4 2	3 5	3 1	2 9	
			0 . 6 7	0 . 8	6 7	5 5	4 7	4 1	6 5	5 4	4 7	4 1	6 2	5 3	4 6	4 1	6 0	5 2	4 5	4 1	3 9	
			0 . 6 3	1 . 0	7 3	6 2	5 5	4 9	7 2	6 2	5 4	4 9	6 9	6 0	5 3	4 8	6 6	5 8	5 3	4 8	4 6	
			1 . 2 5	7 9	6 9	6 2	5 6	7 8	6 9	6 2	5 6	7 4	6 7	6 1	5 6	7 2	6 5	6 0	5 5	5 3		
下方投影面積 等価発光面積		c m ² c m ²	1 . 5	8 3	7 5	6 8	6 2	8 2	7 3	6 7	6 2	7 9	7 2	6 6	6 1	7 6	7 0	6 5	6 1	5 8		
			2 . 0	8 9	8 2	7 6	7 0	8 7	8 0	7 5	7 0	8 4	7 8	7 3	6 9	8 1	7 6	7 2	6 8	6 6		
取付高さ		器具間隔最大限		2 . 5	9 3	8 6	8 1	7 6	9 1	8 5	8 0	7 6	8 8	8 3	7 9	7 5	8 5	8 1	7 7	7 4	7 1	
		横方向 (A) 縦方向 (B)		3 . 0	9 5	9 0	8 5	8 1	9 3	8 8	8 4	8 0	9 0	8 6	8 2	7 9	8 8	8 4	8 1	7 8	7 5	
H m		1 . 2 6 H m 1 . 2 6 H m		4 . 0	9 8	9 4	9 0	8 6	9 7	9 3	8 9	8 6	9 4	9 0	8 7	8 4	9 1	8 8	8 6	8 3	8 0	
				5 . 0	1 0 0	9 7	9 3	9 0	9 9	9 5	9 2	8 9	9 6	9 3	9 0	8 8	9 3	9 1	8 9	8 6	8 4	
				7 . 0	1 0 2	1 0 0	9 7	9 5	1 0 1	9 8	9 6	9 4	9 8	9 6	9 4	9 2	9 6	9 4	9 2	9 1	8 8	
				1 0 . 0	1 0 4	1 0 2	1 0 0	9 9	1 0 3	1 0 1	9 9	9 8	1 0 0	9 9	9 7	9 6	9 8	9 6	9 5	9 4	9 1	

