

屋内照明器具特性	
品番 (品名)	L G B 5 1 5 5 6
光源	LED3500_70_810 ×1 810.0 l m
管理番号	K0142039 (0) DB 1
B Z 分類	B Z 5

器具効率		1 0 0 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %			
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %			
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %			
上方光束		4 %	室指数	照明率 (X 0 . 0 1)																			Z C M	
下方光束		9 6 %																						
保守率		良 中 否	0 . 6 3	0 . 6	0 . 6	0 . 5 6	0 . 6	5 6	4 4	3 6	3 1	5 5	4 3	3 6	3 0	5 2	4 2	3 5	3 0	4 9	4 0	3 4	3 0	2 7
			0 . 6	0 . 8	6 6	5 4	4 7	4 1	6 4	5 4	4 6	4 1	6 1	5 2	4 5	4 0	5 8	5 0	4 4	4 0	3 7			
			0 . 5 6	1 . 0	7 3	6 2	5 4	4 8	7 1	6 1	5 3	4 8	6 7	5 9	5 2	4 7	6 4	5 7	5 1	4 7	4 4			
				1 . 2 5	7 8	6 9	6 1	5 6	7 7	6 8	6 1	5 5	7 3	6 5	5 9	5 4	7 0	6 3	5 8	5 3	5 1			
下方投影面積		c m ²	1 . 5	8 3	7 4	6 7	6 1	8 1	7 2	6 6	6 1	7 7	7 0	6 4	6 0	7 3	6 8	6 3	5 9	5 6				
等価発光面積		c m ²	2 . 0	8 8	8 1	7 5	7 0	8 6	7 9	7 4	6 9	8 2	7 7	7 2	6 8	7 9	7 4	7 0	6 6	6 3				
取付 高さ	器具間隔最大限		2 . 5	9 2	8 5	8 0	7 5	9 0	8 4	7 9	7 5	8 6	8 1	7 7	7 3	8 2	7 8	7 5	7 1	6 8				
	横方向 (A)	縦方向 (B)	3 . 0	9 4	8 9	8 4	8 0	9 2	8 7	8 3	7 9	8 8	8 4	8 0	7 7	8 5	8 1	7 8	7 5	7 2				
H m	1 . 2 7 H m	1 . 2 7 H m	4 . 0	9 7	9 3	8 9	8 5	9 5	9 1	8 8	8 4	9 2	8 8	8 5	8 2	8 8	8 5	8 3	8 0	7 7				
			5 . 0	9 9	9 5	9 2	8 9	9 7	9 4	9 1	8 8	9 4	9 1	8 8	8 6	9 0	8 8	8 6	8 4	8 0				
			7 . 0	1 0 1	9 9	9 6	9 4	1 0 0	9 7	9 5	9 2	9 6	9 4	9 2	9 0	9 3	9 1	8 9	8 8	8 4				
			1 0 . 0	1 0 3	1 0 1	9 9	9 7	1 0 1	9 9	9 8	9 6	9 8	9 6	9 5	9 3	9 5	9 3	9 2	9 1	8 7				

