

屋内照明器具特性

品番 (品名)	LGWC40003K				
光源	LED2700_70_328 x1 328.0 l m				
管理番号	K0128911(0)DB1				
BZ分類	BZ3/0.7/BZ2				

器具効率	100%	天井	80%				70%				50%				30%				0%				
	上方光束		0%	反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%		
	下方光束		100%		床	10%				10%				10%				10%				0%	
室指数		照明率 (X0.01)																				ZCM	
保守率	良	0.63	0.6	0.6	0.56	0.6	66	56	50	45	65	56	50	45	63	55	49	45	61	54	49	45	43
	中	0.6	0.6	0.6	0.6	0.8	77	68	61	57	75	67	61	57	73	66	61	57	71	65	60	56	55
	否	0.56	0.56	0.56	0.56	1.0	83	75	69	65	82	74	69	65	79	73	68	64	77	72	67	64	62
						1.25	88	81	76	72	87	80	75	72	84	79	75	71	82	77	74	71	69
下方投影面積			cm ²		1.5	91	85	80	77	90	84	80	76	88	83	79	76	85	81	78	75	73	
			cm ²		2.0	96	91	87	83	94	90	86	83	92	88	85	82	90	86	84	81	79	
取付高さ	器具間隔最大限				2.5	98	94	91	87	97	93	90	87	95	91	88	86	92	90	87	85	83	
	横方向 (A)		縦方向 (B)		3.0	100	96	93	91	99	95	92	90	96	93	91	89	94	92	90	88	85	
Hm	1.23Hm		1.23Hm		4.0	102	99	97	95	101	98	96	94	99	96	94	93	96	94	93	91	89	
					5.0	103	101	99	97	102	100	98	96	100	98	96	95	98	96	95	93	91	
				7.0	105	103	102	100	104	102	101	99	101	100	99	98	99	98	97	96	93		
				10.0	106	105	104	102	105	104	103	102	102	101	101	100	100	99	99	98	95		

