

屋内照明器具特性

品番 (品名)	LSBJ 50002																
光源	LED2700_70_3 ×1 3.0 lm																
管理番号	K0130298(0)DD1																
BZ分類	BZ10																

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
		床	10%				10%				10%				10%				0%	
上方光束	50%																			
下方光束	50%																			
室指数	照明率 (X0.01) ZCM																			
保守率	良 中 否	0.63	0.6	42	29	21	15	38	27	19	14	31	22	15	11	24	17	12	8	3
		0.6	0.8	50	37	28	22	46	34	26	20	37	28	21	16	29	22	17	13	6
		0.56	1.0	56	44	34	28	51	40	32	25	41	32	26	21	32	26	20	16	8
			1.25	62	50	41	34	56	45	37	31	46	37	31	26	36	29	24	20	11
下方投影面積		cm ²																		
等価発光面積		cm ²																		
取付高さ	器具間隔最大限		2.5	75	66	59	53	69	61	54	49	57	51	45	41	46	41	37	33	21
	横方向 (A)	縦方向 (B)	3.0	78	70	63	57	72	65	58	53	59	54	49	45	48	44	40	36	23
H _m	0.00H _m	1.55H _m	4.0	82	75	69	64	75	69	64	59	63	58	54	50	51	47	44	41	27
			5.0	84	79	73	69	78	73	68	64	65	61	57	54	53	50	47	44	30
			7.0	87	83	78	75	81	77	73	69	68	65	62	59	56	53	51	49	34
			10.0	90	86	83	80	83	80	77	74	70	68	66	63	58	56	55	53	37

