

# 屋内照明器具特性

品番 (品名)	LSEB2022														
光源	LED2700_70_2315 x1 2315.0 lm														
管理番号	K0140345(0)DR1														
BZ分類	BZ5														

器具効率	100%	天井	80%				70%				50%				30%				0%	
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%
上方光束	7%	反射率	床	10%				10%				10%				10%				0%
下方光束	93%		室指数	照明率 ( X0.01) ZCM																
保守率	良 中 否 0.63 0.6 0.56	0.6	55	43	35	30	53	42	35	29	50	40	34	29	48	39	33	28	26	
		0.8	65	53	45	39	63	52	44	39	59	50	43	38	56	48	42	37	35	
		1.0	71	60	52	46	69	59	52	46	65	57	50	45	62	54	49	44	41	
		1.25	77	67	59	53	75	66	58	53	71	63	57	52	67	60	55	51	47	
下方投影面積	c m <sup>2</sup>	1.5	81	72	65	59	79	70	64	58	75	67	62	57	71	65	60	56	52	
		2.0	87	79	72	67	84	77	71	66	80	74	69	64	76	71	67	63	59	
取付高さ	器具間隔最大限		2.5	90	83	77	73	88	82	76	72	83	78	74	70	79	75	71	68	64
	横方向 (A)	縦方向 (B)	3.0	93	86	81	77	90	85	80	76	86	81	77	74	82	78	75	72	68
H m	1.25 H m	1.25 H m	4.0	96	91	86	83	93	89	85	81	89	86	82	79	85	82	79	77	73
			5.0	98	94	90	86	96	92	88	85	91	88	85	83	87	85	82	80	76
			7.0	100	97	94	91	98	95	92	90	94	91	89	87	90	88	86	84	80
			10.0	102	100	97	95	100	98	96	94	96	94	92	91	92	91	89	88	83

