

屋内照明器具特性	
品番 (品名)	F Y Y 2 6 0 3 0
光源	LED3000_85_2680 ×1 2680.0 lm
管理番号	K0149007 (0) DB 1
B Z 分類	B Z 5

器具効率		100 %	天井 壁 床	80 %				70 %				50 %				30 %				0 %			
				70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %			
				10 %				10 %				10 %				10 %				0 %			
上方光束 下方光束		8 % 92 %	反射率	照明率 (X0.01) Z CM																			
保守率		良 中 否	室指数	0.6	54	42	34	28	53	41	34	28	49	39	33	28	47	38	32	27	25		
				0.8	64	52	44	38	62	51	43	38	58	49	42	37	55	47	41	36	33		
				1.0	71	59	51	45	68	58	51	45	64	56	49	44	61	53	47	43	40		
				1.25	76	66	58	53	74	65	58	52	70	62	56	51	66	59	54	49	46		
下方投影面積 等価発光面積		cm ² cm ²	室指数	1.5	80	71	64	58	78	69	63	57	74	66	61	56	70	63	58	54	51		
				2.0	86	78	71	66	84	76	70	65	79	73	68	63	75	70	65	62	58		
取付 高さ	器具間隔最大限		室指数	2.5	90	83	77	72	87	81	75	71	83	77	73	69	78	74	70	67	62		
	横方向 (A) 縦方向 (B)			3.0	92	86	81	76	90	84	79	75	85	80	76	73	81	77	73	70	66		
1.5m	2.22 m	2.32 m	4.0	95	90	86	82	93	88	84	81	88	85	81	78	84	81	78	76	71			
2	2.94	3.01	5.0	97	93	89	86	95	91	88	84	91	87	84	82	86	84	81	79	74			
2.5	3.66	3.71	7.0	100	96	93	91	97	94	92	89	93	91	88	86	89	87	85	83	78			
3	4.39	4.42	10.0	102	99	97	95	99	97	95	93	95	93	91	90	91	90	88	87	82			

