

屋内照明器具特性	
品番 (品名)	NNN15430
光源	LDA7L-G/S/K6 ×3 810.0 lm
管理番号	K0178581 (0) DR 1
BZ分類	BZ9

器具効率		6 2 %	反射率	天井	8 0 %				7 0 %				5 0 %				3 0 %				0 %
				壁	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	7 0	5 0	3 0	1 0	0 %
				床	1 0 %				1 0 %				1 0 %				1 0 %				0 %
				室指数	照明率 (X 0 . 0 1)																
保守率		良 中 否	0 . 6 9	0 . 6	2 7	2 0	1 5	1 1	2 5	1 8	1 3	1 0	2 0	1 5	1 1	8	1 6	1 2	9	7	3
			0 . 6 7	0 . 8	3 3	2 5	2 0	1 6	3 0	2 3	1 8	1 5	2 4	1 9	1 5	1 2	1 9	1 5	1 2	1 0	6
			0 . 6 3	1 . 0	3 6	2 9	2 3	1 9	3 3	2 6	2 2	1 8	2 7	2 2	1 8	1 5	2 2	1 8	1 5	1 2	7
				1 . 2 5	4 0	3 3	2 7	2 3	3 6	3 0	2 5	2 2	3 0	2 5	2 1	1 8	2 4	2 0	1 7	1 5	9
下方投影面積		c m ²		1 . 5	4 2	3 6	3 1	2 6	3 9	3 3	2 8	2 4	3 2	2 7	2 4	2 1	2 5	2 2	1 9	1 7	1 0
			等価発光面積	c m ²	2 . 0	4 6	4 0	3 5	3 1	4 2	3 7	3 3	2 9	3 5	3 1	2 7	2 5	2 8	2 5	2 2	2 0
取付 高さ	器具間隔最大限			2 . 5	4 8	4 3	3 9	3 5	4 4	3 9	3 6	3 2	3 7	3 3	3 0	2 7	3 0	2 7	2 5	2 2	1 5
	横方向 (A)	縦方向 (B)		3 . 0	5 0	4 5	4 1	3 8	4 6	4 2	3 8	3 5	3 8	3 5	3 2	3 0	3 1	2 9	2 6	2 4	1 6
1 . 5 m	2 . 2 1 m	2 . 3 3 m		4 . 0	5 2	4 8	4 5	4 2	4 8	4 4	4 1	3 9	4 0	3 7	3 5	3 3	3 3	3 1	2 9	2 7	1 8
2	2 . 9 4	3 . 0 8		5 . 0	5 3	5 0	4 7	4 4	4 9	4 6	4 4	4 1	4 1	3 9	3 7	3 5	3 4	3 2	3 1	2 9	2 0
2 . 5	3 . 6 6	3 . 8 3		7 . 0	5 5	5 2	5 0	4 8	5 1	4 9	4 6	4 4	4 3	4 1	3 9	3 8	3 6	3 4	3 3	3 2	2 2
3	4 . 3 9	4 . 6		1 0 . 0	5 6	5 4	5 3	5 1	5 2	5 0	4 9	4 7	4 4	4 3	4 2	4 0	3 7	3 6	3 5	3 4	2 4

