

# 屋内照明器具特性

品番(品名)	NND2 6 2 2 0 Z	
光源	NND2 6 2 2 0 Z (ALL) ×1      600.0 l m	
管理番号	K0128724 (3) DB 1	
BZ分類	BZ1	

器具効率	100 %	天井	80 %				70 %				50 %				30 %				0 %		
			壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
上方光束	0 %	床	10 %				10 %				10 %				10 %				0 %		
下方光束	100 %		室指数																		
		照明率 ( ×0.01 )																		Z C M	
保守率	良	0.45	0.6	99	97	95	94	99	96	95	94	98	96	95	94	97	96	94	94	93	
	中	0.43	0.8	101	99	97	96	101	99	97	96	100	98	97	96	99	98	96	96	95	
	否	0.4	1.0	103	100	99	98	102	100	99	98	101	99	98	97	100	99	98	97	96	
下方投影面積	c m <sup>2</sup>	等価発光面積	c m <sup>2</sup>	1.25	1.04	1.02	1.00	99	1.03	1.01	1.00	99	1.02	1.00	99	1.01	1.00	99	98	97	
				1.5	1.04	1.03	1.01	1.00	1.04	1.02	1.01	1.00	1.02	1.01	1.00	99	1.01	1.00	99	99	97
取付高さ	器具間隔最大限		H m	0.29 H m	0.28 H m	2.5	1.06	1.05	1.04	1.03	1.05	1.04	1.03	1.02	1.04	1.03	1.02	1.01	1.01	0.99	
	横方向 (A)	縦方向 (B)				3.0	1.06	1.05	1.05	1.04	1.06	1.05	1.04	1.03	1.04	1.03	1.02	1.02	1.02	1.01	1.01
H m	0.29 H m	0.28 H m	4.0	1.07	1.06	1.05	1.05	1.06	1.05	1.05	1.04	1.04	1.04	1.03	1.03	1.02	1.02	1.02	1.01	0.99	
			5.0	1.07	1.07	1.06	1.06	1.06	1.06	1.05	1.05	1.04	1.04	1.04	1.03	1.03	1.02	1.02	1.02	1.01	0.99
H m	0.29 H m	0.28 H m	7.0	1.08	1.07	1.07	1.06	1.07	1.06	1.06	1.06	1.05	1.04	1.04	1.04	1.03	1.03	1.02	1.02	1.00	
			10.0	1.08	1.08	1.07	1.07	1.07	1.07	1.06	1.06	1.05	1.05	1.05	1.04	1.03	1.03	1.03	1.03	1.01	0.99

