

屋内照明器具特性	
品番 (品名)	NNF J 4 1 8 0 9
光源	LDL40T. Y/ 17/ 21- S ×1 2150.0 lm
管理番号	K0145602 (2) DB 1
B Z 分類	BZ6/ 0.7/ BZ5

器具効率		95 %	反射率	天井	80 %					70 %					50 %					30 %					0 %	
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %	
					床	10 %					10 %					10 %					10 %					0 %
						室指数	照明率 (X0.01)																			
保守率		良 中 否	0.77	0.6	51	39	31	26	49	38	31	26	46	37	30	25	44	35	29	25	22					
			0.72	0.8	60	49	41	35	58	48	40	35	55	46	39	34	52	44	38	33	31					
			0.68	1.0	66	56	48	42	64	54	47	41	60	52	46	41	57	50	44	40	37					
				1.25	72	62	55	49	70	61	54	48	66	58	52	47	62	55	50	46	43					
下方投影面積		cm ²	1.5	76	67	60	54	74	65	59	53	69	62	57	52	66	60	55	51	47						
			等価発光面積	cm ²	2.0	81	74	67	62	79	72	66	61	75	69	64	59	71	66	61	58	54				
取付 高さ	器具間隔最大限		2.5	85	78	72	67	82	76	71	66	78	73	68	65	74	70	66	63	59						
	横方向 (A)	縦方向 (B)	3.0	87	81	76	72	85	79	75	71	81	76	72	68	77	73	69	66	62						
1.5m	2.09 m	2.15 m	4.0	90	86	81	77	88	84	80	76	84	80	77	74	80	77	74	72	67						
2	2.77	2.72	5.0	92	88	85	81	90	86	83	80	86	83	80	77	82	80	77	75	71						
2.5	3.44	3.31	7.0	95	92	89	86	93	90	87	85	89	86	84	82	85	83	81	79	75						
3	4.11	3.91	10.0	97	94	92	90	94	92	90	88	90	89	87	85	87	85	84	82	78						

