

屋内照明器具特性	
品番 (品名)	NNN6 1 5 1 1 WZ
光源	LDA7 L - H / S / 6 × 1 810.0 l m
管理番号	K0178345 (0) DB 1
B Z 分類	BZ3

器具効率		58 %	反射率	天井	80 %					70 %					50 %					30 %					0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %				
				床	10 %					10 %					10 %					10 %					0 %
				室指数	照明率 (X0.01) Z C M																				
保守率		良 中 否	0.67	0.6	38	32	28	25	37	31	28	25	36	31	28	25	35	30	27	25	24				
			0.63	0.8	43	38	34	31	42	37	34	31	41	37	34	31	40	36	33	31	30				
			0.56	1.0	47	42	38	36	46	41	38	35	45	41	38	35	43	40	37	35	34				
				1.25	50	45	42	39	49	45	42	39	47	44	41	39	46	43	41	39	38				
下方投影面積		c m ²		1.5	52	48	45	42	51	47	44	42	49	46	44	42	48	45	43	41	40				
			等価発光面積	c m ²	2.0	54	51	48	46	54	51	48	46	52	49	47	46	51	48	47	45	44			
取付 高さ	器具間隔最大限			2.5	56	53	51	49	55	53	50	49	54	52	50	48	52	50	49	48	46				
	横方向 (A) 縦方向 (B)			3.0	57	55	53	51	56	54	52	51	55	53	51	50	53	52	50	49	48				
H m	1.10 H m	1.10 H m		4.0	58	57	55	53	58	56	54	53	56	55	53	52	55	54	53	52	50				
				5.0	59	58	56	55	58	57	56	55	57	56	55	54	56	55	54	53	51				
				7.0	60	59	58	57	59	58	57	57	58	57	56	56	57	56	55	55	53				
				10.0	61	60	59	59	60	59	59	58	59	58	58	57	57	57	56	56	54				

