

屋内照明器具特性	
品番 (品名)	NNN6 1 5 1 1 WZ
光源	LDA4 L - G / K4 ×1 485.0 lm
管理番号	K0178348 (0) DB 1
B Z 分類	BZ3

器具効率		59 %	反射率	天井	80 %				70 %				50 %				30 %				0 %
				壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
				床	10 %				10 %				10 %				10 %				0 %
				室指数	照明率 (X0.01)																Z
保守率		良 中 否	0.67	0.6	37	31	27	25	37	31	27	25	36	30	27	24	34	30	27	24	23
			0.63	0.8	43	38	34	31	42	37	34	31	41	36	33	31	40	36	33	31	29
			0.56	1.0	47	42	38	35	46	41	38	35	45	40	37	35	43	40	37	35	34
				1.25	50	45	42	39	49	45	42	39	48	44	41	39	46	43	41	39	37
下方投影面積		cm ²		1.5	52	48	45	42	51	47	44	42	50	46	44	42	48	46	43	41	40
				2.0	55	51	49	46	54	51	48	46	52	50	48	46	51	49	47	45	44
等価発光面積		cm ²		2.5	56	54	51	49	56	53	51	49	54	52	50	48	53	51	49	48	46
				3.0	58	55	53	51	57	55	53	51	55	53	52	50	54	52	51	50	48
H	m	1.15 H	m	1.15 H	m	4.0	59	57	55	54	58	56	55	53	57	55	54	53	52	50	
						5.0	60	58	57	56	59	58	56	55	58	56	55	54	53	52	
						7.0	61	60	59	58	60	59	58	57	59	58	57	56	55	54	
						10.0	62	61	60	59	61	60	59	59	59	58	58	58	57	55	

