

屋内照明器具特性	
品番 (品名)	NNN14000
光源	NNN14000 ×1 1155.0 lm
管理番号	K0130340(2)DB1
BZ分類	BZ5

器具効率	100%	天井	80%				70%				50%				30%				0%	
		壁	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0%	
上方光束	13%	床	10%				10%				10%				10%				0%	
下方光束	87%	室指数	照明率 (×0.01)																ZCM	
保守率	良 中 否 0.63 0.6 0.56	0.6	5.4	4.2	3.4	2.8	5.2	4.0	3.3	2.8	4.8	3.8	3.2	2.7	4.5	3.6	3.0	2.6	2.3	
		0.8	6.3	5.2	4.4	3.8	6.1	5.0	4.3	3.7	5.7	4.8	4.1	3.6	5.3	4.5	3.9	3.5	3.2	
		1.0	7.0	5.9	5.1	4.5	6.7	5.7	5.0	4.4	6.3	5.4	4.8	4.3	5.8	5.1	4.6	4.1	3.8	
		1.25	7.6	6.6	5.8	5.2	7.3	6.4	5.7	5.1	6.8	6.0	5.4	5.0	6.4	5.7	5.2	4.8	4.4	
下方投影面積	c m ²	1.5	8.0	7.1	6.3	5.8	7.7	6.9	6.2	5.7	7.2	6.5	5.9	5.5	6.7	6.1	5.7	5.3	4.8	
		2.0	8.5	7.8	7.1	6.6	8.3	7.5	7.0	6.5	7.7	7.1	6.6	6.2	7.2	6.8	6.3	6.0	5.5	
取付高さ	器具間隔最大限		2.5	8.9	8.2	7.7	7.2	8.6	8.0	7.5	7.0	8.1	7.6	7.1	6.7	7.6	7.2	6.8	6.5	6.0
	横方向 (A)	縦方向 (B)	3.0	9.1	8.6	8.0	7.6	8.9	8.3	7.9	7.4	8.3	7.9	7.5	7.1	7.8	7.5	7.1	6.8	6.3
H m	1.26 H m	1.26 H m	4.0	9.5	9.0	8.6	8.2	9.2	8.7	8.4	8.0	8.6	8.3	8.0	7.7	8.1	7.9	7.6	7.3	6.8
			5.0	9.7	9.3	8.9	8.6	9.4	9.0	8.7	8.4	8.9	8.6	8.3	8.0	8.4	8.1	7.9	7.7	7.4
			7.0	9.9	9.6	9.3	9.0	9.6	9.3	9.1	8.8	9.1	8.9	8.7	8.5	8.6	8.4	8.2	8.1	7.5
			10.0	10.1	9.9	9.6	9.4	9.8	9.6	9.4	9.2	9.3	9.1	9.0	8.8	8.8	8.7	8.5	8.4	7.8

