

屋内照明器具特性	
品番 (品名)	NNN6 1 5 1 3 WK
光源	LDA7L - H/ S/ 6 ×1 810.0 lm
管理番号	K0178353 (0) DB 1
B Z 分類	BZ3

器具効率	72 % 上方光束 0 % 下方光束 72 %	天井	80 %				70 %				50 %				30 %				0 %
		反射率	70	50	30	10	70	50	30	10	70	50	30	10	70	50	30	10	0 %
		壁	10 %				10 %				10 %				10 %				0 %
		床	照明率 (X0.01)				Z CM												
保守率	良 0.67 中 0.63 否 0.56	室指数	46	39	34	30	45	38	33	30	44	37	33	30	42	37	33	30	29
		0.6	54	47	42	38	53	46	42	38	51	45	41	38	49	44	41	38	37
		0.8	58	52	47	44	57	51	47	44	55	50	47	44	54	49	46	43	42
		1.0	62	56	52	49	61	56	52	49	59	55	51	49	57	54	51	48	47
下方投影面積 等価発光面積	cm ² cm ²	1.25	65	60	56	53	64	59	55	52	62	58	55	52	60	57	54	52	50
		1.5	68	64	61	58	67	63	60	58	65	62	59	57	63	61	58	56	55
		2.0	70	67	64	61	69	66	63	61	67	65	62	60	65	63	61	59	58
		2.5	71	68	66	64	70	68	65	63	69	66	64	62	67	65	63	62	60
取付高さ H m	器具間隔最大限		73	71	69	67	72	70	68	66	70	69	67	65	69	67	66	65	63
	横方向 (A)	縦方向 (B)	74	72	71	69	73	72	70	68	72	70	69	67	70	69	67	66	64
	1.25 H m	1.25 H m	75	74	73	71	75	73	72	71	73	72	71	70	71	70	69	69	67
			76	75	74	73	75	74	74	73	74	73	72	71	72	71	71	70	68

